



### OFFICIAL LISTING

NSF International Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI Standard 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on June 20, 2011.

Enecon Corporation  
6 Platinum Court  
Medford, NY 11763  
800-436-3266  
516-349-0022



Facility: Medford, NY

Trade Designation	Protective (Barrier) Materials		Water Contact Temp	Water Contact Material
	Water Contact Size Restriction			
<b>Coatings - Fittings</b> CHEMCLAD® XC <sup>[1]</sup>	>= 6"		CLD 23	EPOXY
<b>Coatings - Pipe</b> CHEMCLAD® XC <sup>[1]</sup>	>= 12"		CLD 23	EPOXY
<b>Coatings - Pump</b> CHEMCLAD® XC <sup>[1]</sup>	>= 4"		CLD 23	EPOXY
<b>Coatings - Tank</b> CHEMCLAD® XC <sup>[1]</sup>	>= 75 gal.		CLD 23	EPOXY
<b>Coatings - Valve</b> CHEMCLAD® XC <sup>[1]</sup>	>= 6"		CLD 23	EPOXY

[1] Colors: Light gray, white  
Number of Coats: 2 - 4  
Maximum Field Use Dry Film Thickness (in mils): 24  
Maximum Thinner: None  
Recoat Cure Time and Temperature: 4 hours at 77°F  
Final Cure Time and Temperature: 4 days at 77°F  
Special Comments: Mix ratio of A:B is 5:3 by weight.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.